

TECHNICAL DATA SHEET

Cooling System Stop Leak

Systac Cooling System Stop Leak is a complex formulation of several sealing components that together guarantee a sealing functioning. It stops leakages from the radiator, the hoses and the small cracks in the water jacket and cylinder head. It also contains anti-corrosive ingredients.

Assets of the product

Systac Cooling System Stop Leak offers the following advantages if used according to specifications:

- As long as **Systac Cooling System Stop Leak** is present in the system, it will continue to search for leakages.
- Does not give unwanted deposits in the cooling system.
- Due to its unique formulation, the seal will only harden after contact with the outdoor air. This will prevent blockages in the system.
- Extremely suitable to quickly and effectively seal a leakage of the cooling system in case of emergency.
- Provides a permanent solution for smaller leakages.
- Prevents rust and boiler scale, and lubricates the water pump.

Available packaging

SYS-CSS-90018 – 500 ML

Instructions

Check the cooling system for contamination and clean it first with **Systac Cooling System Degreaser** or **Systac Cooling System Cleaner**, if necessary.

Shake the flask well before use. Add **Systac Cooling System Stop Leak** to a warm cooling system and open the heating valve if available. Afterwards, allow the engine to idle for at least 15 minutes at an increased idle state. Fill the cooling system with a coolant as specified by the manufacturer. Verify the complete cooling system for correct operation after treatment.

Dosage: 5 vol.% of the total cooling system.

If you have any questions, please consult your advisor.