

Tel.: (+31)497 - 38 48 47 E-mail: info@systac.nl Rootven 10 5531 MB BLADEL The Netherlands

TECHNICAL DATA SHEET

Petrol System Cleaner

Systac Petrol System Cleaner is specially formulated product designed to effectively clean and maintain the entire petrol fuel system of the combustion engines. It also removes contamination that is caused by combustion in the combustion chamber and ensures the optimal operation of lambda probes and catalysts. Safe for the latest exhaust gas followup treatment systems including the particulate filter. Extremely suitable for hybrid vehicles.

Assets of the product

Systac Petrol System Cleaner offers the following benefits when used as instructed:

- The product is suitable for fuel systems which are directly and indirectly injected as well as carburetors.
- The product is completely miscible and harmless for fuels containing bioethanol up to and including E20.
- The product can be used safely with exhaust gas follow-up treatment systems such as catalysts and particulate filters.
- The product keeps the fuel system in perfect condition during maintenance and ensures that the fuel metering is not adversely affected by lacquer and varnish deposits.
- Counteracts ageing and acidification during the storage of petrol.
- Prevents the formation of corrosion in the tank and in the fuel system.
- Cleans the combustion chamber and the piston crown during use.
- Can reduce fuel consumption due to an improved mixture preparation.
- Ensures an optimal combustion and an optimal operation of the exhaust gas follow-up treatment system.

Instructions

1 dosage of 500 ml is sufficient for 20 to 60 litres of fuel during maintenance.

In case of severe contamination, use 1 dosage per 5 L - 15 litres of fuel. Do a test ride of at least 30 minutes and make sure the engine warms up well.

In case of malfunction: make sure the engine is warmed up and let the engine run on undiluted **Systac Petrol System Cleaner**. (A rinse tank with possible pressure supply). After that, add one dose of **Systac Petrol Cleaner** to the content of the fuel tank and do a test ride of at least 25 km.

Consult your advisor in case of questions.

Available packaging

SYS-PSC-90005 - 400 ML